



[Traffic Curtains](#)



PVC Rolls




["Shower style" Curtains](#)



[Impact Traffic Doors](#)

 Chase Doors



PVC Rolls

Strip meets:

- USDA Federal requirements for contact with meat, poultry or dairy products;
- CPAI-84 and California State Fire Marshal requirements for flame resistance (registered F-209 standard and welding only).

Strips are generally resistant to inorganic acids, bases and salts. However they can be affected by Ketones and Esthers. Therefore, all specific applications should be tested by user for effects on material.

Products and characteristics recap :

Products	Width x Thickness x Length	Maximum Height	Additional Information
Standard	06" x 0,060" x 300' 08" x 0,080" x 300' 12" x 0,120" x 200' 16" x 0,160" x 100' 48" x 0,080" x 60'	08' 10' 15' 20' n/a	Stays flexible in room temperature; personnel doors use; interior opening; for lift traffic, use ribbed strips.
Anti-static	08" x 0,080" x 300' 12" x 0,120" x 150'	10' 15'	Formulated to dissipate static electricity harmlessly away from sensitive equipment or material (examples : computer room, fireworks factory, etc.).
Low temp.	06" x 0,060" x 300' 08" x 0,080" x 300' 12" x 0,120" x 200' * 16" x 0,160" x 100' * 48" x 0,080" x 60' *	08' 10' 15' * 20' * n/a	Remains flexible in cold weather; recommended for coolers and freezers; for lift traffic, use ribbed strips.
Low temp. ribbed	08" x 0,080" x 150' 12" x 0,120" x 150'	10' 15'	40% more resistant; highly recommended with 100% overlap strips; for high traffic area of heavy machinery; near cellophane skid packaging; also for garage door use.
Standard / security (orange)	08" x 0,080" x 300'	10'	Useful to delimit the center and/or each side of an opening.
Standard / welding (ambre, orange or opaque black)	08" x 0,080" x 300'	10'	Protect against harmful UV rays, sparks and welding fumes.

* Available on request only

For quotations / orders, call us !